## Listing of Claims:

Claims 1-7. (Canceled)

8. (Currently Amended) A first subscriber identifying module including a microcontroller in a mobile telecommunication network which is configured to communicate with at least one remote system in the mobile telecommunication network, said first subscriber identifying module and said remote system being adapted to store at least one parameter identifying a user in the network, said first subscriber identifying module comprising:

a one-time account identifier designed for a one-time logon to the network; [[and]] a permanent account identifier, said permanent account identifier being deactivated <u>and</u>

another permanent account identifier, said another permanent account identifier being activated and attached to a second subscriber identifying module, wherein the another permanent account identifier is copied from the second subscriber identifying module to the first subscriber identifying module;

wherein said one-time and <u>another</u> permanent account identifier are prestored in said at least one remote system, and

wherein said microcontroller is programmed to:

attached to the first subscriber identifying module; and

- a) use the one-time account identifier to logon to the network when said first subscriber identifying module is switched on;
- b) exchange the one-time account identifier with the permanent account identifier in the first subscriber identifying module upon successful logon to the network as the active account identifier in the first subscriber identifying module; and

c) upon successful logon to the network, send an activation request <u>including the</u>

<u>permanent account identifier and the another permanent account identifier to said at least one</u>

<u>remote network</u> for deactivating in said at least one remote network the <u>another</u> permanent

account identifier attached to the [[first]] second subscriber identifying module,

wherein the step b) is performed in said first subscriber identifying module by an autoactivation application executed after receiving a message from the network informing a successful logon.

#### (Canceled)

10. (Currently Amended) The first subscriber identifying module according to claim 8, wherein the permanent account identifier attached to the first subscriber identifying module identifies an account which is different from an account identified by [[an]] the another permanent account identifier attached to [[a1]] the second subscriber identifying module.

## 11. (Canceled)

- (Previously Presented) The first subscriber identifying module according to claim 8, wherein said first subscriber identifying module is a SIM card.
- 13. (Currently Amended) The first subscriber identifying module according to claim 8, wherein the logon step a) is performed in a centralized remote system and, after receiving the activation request from said first subscriber identifying module, said centralized remote system

sends commands to said at least one remote system for exchanging [[the]] <u>a</u> current active account corresponding to <u>the another permanent account identifier attached to [[a]] the</u> second subscriber identifying module into [[the]] <u>a</u> new active account corresponding to <u>the permanent</u> account identifier attached to the first subscriber identifying module.

#### 14. (Canceled)

15. (Currently Amended) A remote telecommunication system in a mobile telecommunication network, wherein the remote telecommunication system is configured for communicating with a subscriber identifying module, said remote telecommunication system storing:

a one-time account identifier for a one-time logon of a first subscriber identifying module to the network:

a permanent account identifier which is activated and attached to a second subscriber identifying module; and

a set of instructions for accepting logon of the first subscriber identifying module in the network with the one-time account identifier and treating an activation request including the permanent account identifier and another account identifier, which is deactivated and attached to the first subscriber identifying module, sent from an auto-activation application executed in the first subscriber identifying module by the following operations:

deactivating the permanent account identifier attached to the second subscriber identifying module and activating the one-time another permanent account identifier attached to the first subscriber identifying module.

- 16. (Previously Presented) The remote telecommunication system according to claim 15, wherein the remote telecommunication system is programmed for associating the permanent account identifier attached to the second subscriber identifying module with the same account as the account identified by the one-time account identifier attached to the first subscriber identifying module.
- 17. (Currently Amended) The remote telecommunication system according to claim 15, wherein the remote telecommunication system is programmed for associating [[a]] the another permanent account identifier attached to the first subscriber identifying module to an account which is different from the account identified by the permanent account identifier attached to the second subscriber identifying module.
- 18. (Previously Presented) The remote telecommunication system according to claim 15, wherein the remote system determines the account identifier to be deactivated from the permanent account identifier attached to the second subscriber identifying module as transmitted by the first subscriber identifying module.
- 19. (Previously Presented) The remote telecommunication system according to claim 15, wherein the one-time account identifier is the same for a set of subscriber identifying modules in the network.

 (Currently Amended) A method for activating a subscriber identifying module in a telecommunication network, said method comprising the steps of:

providing a first subscriber identifying module which stores a one-time account identifier designed for a one-time logon to the network, and which also-stores a permanent account identifier, said permanent account identifier being deactivated, and another permanent account identifier, said another permanent account identifier being activated and attached to a second subscriber identifying module, wherein the another permanent account identifier is copied from the second subscriber identifying module to the first subscriber identifying module, said first subscriber identifying module being programmed to automatically, upon successful one-time logon to the network, exchange the one-time account identifier with the permanent account identifier in said first subscriber identifying module and send an activation request including the permanent account identifier and the another permanent account identifier to a remote network system for activating said permanent account identifier attached to the first subscriber identifying module; and

providing a remote network system which stores [[an]] the another permanent [[active]] account identifier attached to [[a]] the second subscriber identifying module, said remote network system being programmed for treating the activation request originating from the first subscriber identifying module by the operations which include deactivating the another permanent account identifier attached to the second subscriber identifying module and activating the account identifier attached to the first subscriber identifying module.

# 21. - 30. (Canceled)